

SAP006

常壓式電漿清潔設備



項目	Remote Type		
	SAP006R(G3)	SAP006R(G5)	SAP006R(G8)
電漿寬度	550mm	1100mm	2200mm
電漿頭尺寸 (W*D*H)	900mm*210mm*300mm	1450mm*210mm*300mm	2550mm*210mm*300mm
重量	25kg(55.11lbs)	50kg(110.23lbs)	100kg(220.46lbs)
需求電源	220V, 60 Hz, 1phase, 3wire,15A, 地線<5Ω	220V, 60 Hz, 1phase,3wire, 30A, 地線<5Ω	220V, 60 Hz, 1phase, 3wire,60A, 地線<5Ω
電漿輸出功率 (註 1)	1600~1800W	3200~3500W	6500~7000W
電漿有效距離	1~3mm (建議 2mm)		
進氣接頭	12 * 8mm Connector		
N2 壓力	5.5±0.5kg/cm ²		
N2 流量	385L/min	770L/min	1540L/min
控制介面	Display and Button		

SAP006

常壓式電漿清潔設備

項目		Direct Type		
		SAP006B(G3)	SAP006B(G5)	SAP006B(G8)
1	電漿寬度	550mm	1100mm	2200mm
2	電漿頭尺寸 (W*D*H)	900mm*210mm*300mm	1450mm*210mm*300mm	2550mm*500mm*460mm
3	重量	25kg	50kg	100kg
4	需求電源	220V, 60 Hz, 1phase, 3wire,15A, 地線<5Ω	220V, 60 Hz, 1phase, 3wire, 30A, 地線<5Ω	220V, 60 Hz, 1phase, 3wire,60A, 地線<5Ω
5	電漿輸出功率 (註 1)	500~700W	1000~1300W	2000~2500W
6	電漿有效距離	1~3mm (建議 2mm)		
7	進氣接頭	12 * 8mm Connector		
8	N2 壓力	5.5±0.5kg/cm ²		
9	N2 流量	5.5L/min	11L/min	22L/min
10	控制介面	Display and Button		
項目		其他配件		
1	調壓閥	Standard		
2	鼓風機	Standard		
3	抽氣罩	Standard		
6	三色燈	Optional		
7	N2 Generator	Optional		

Reference :Caution : Design will not support by External Power Control (EPC)